

ROCKMAX[®] ADHESIVE 11

ADHESIVE FOR INSTALLATION RUBBER WATERSTOP



INTRODUCTION

Rockmax Adhesive 11 is a one part, ready to use contact adhesive based on polychloroprene. It can be used for installation hydrophilic rubber waterstops on dry concrete substrates.

AREA OF USES

Rockmax Adhesive 11 can be used as adhesive for hydrophilic rubber waterstops on dry concrete substrates.

ADVANTAGES

- Good bonding and adhesive.
- Fast drying.
- Easy to use.

TECHNICAL PROPERTIES

Appearance: Viscous yellow liquid
Density: 870 kg/m³
Drying time (at 25 C): approx 15 minute
Flash point: -12 °C degree
Fire point: 250 °C degree
Boiling point: 70 °C degree
Application Temperature: +10°C to +45°C
Services Temperature: +5°C to +70°C
Coverage: 250gram per 1 m²
(apply one side)

PREPARATION

The concrete substrate must be sound, clean, dry and free from oil, mould oil, grease, dust, dirt, cement paste and loose contaminants. In case of dust and dirt we recommended clean by compressed air. Do not use water to clean.

APPLICATION

Apply **Rockmax Adhesive 11** by brush on both adhere surface. All area of surface to bond must be cover with adhesive. Wait the adhesive to initial cure (or touch dry) at approximate 5-10 minutes depend on ambient temperature but no longer than 30 minutes. Press the rubber waterstop on the surface with constant pressure along the length of the joint. Use rubber hammer or steel roller for making rubber waterstop perfectly attached to the concrete surface. Allow the adhesive to cure at approximate 30 minute. Fully cure in 24 hours.

CLEANING

Clean all tools and equipments immediately with thinner with dampened clothes.

PACKAGING

650 gram
15kg

STORAGE

Storage in cool and dry condition free from frost, water, moisture and high temperature. Avoid sunlight. Keep container tightly from air or moisture. Storage at temperate below 30°C degree.

SHELF LIFE

9 months if kept follow instructions.

PRECAUTIONS

The material is flammable. Avoid contact with skin and eye. Avoid inhalation. Harmful effects may cause during application and care must be taken. Do not expose to flames or other sources of ignition, sparks or fire. No smoking allowance. Ventilation must be provided. Keep out of reach of children. MSDS is available upon request.

CONTACT DETAIL

THAILAND

Rockmax Company Limited

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

VIETNAM

Viet Dai Viet Chemical Company Limited

T: +84 86 2615184

F: +84 86 2615185

E: rockmaxvn@gmail.com

IMPORTANT NOTE!!

The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.