

# ROCKMAX<sup>®</sup> PUTTY

## ACRYLIC WALL PUTTY



### INTRODUCTION

**Rockmax Putty** is a waterborne, acrylic putty for interior and exterior use. It has excellent resistance to adverse weather conditions, damp, alkalinity and is suitable for coating of plaster, concrete, cement boards, plaster boards, gypsum boards. The material is smooth and fine surface, Easy to work and quick drying without cracks.

### AREA OF USES

**Rockmax Putty** can be used to fill the holes, voids, joints, cracks, seams for concrete, gypsum boards, cement boards, plaster boards, woods, brick works, block works, mortars, tiles.

### ADVANTAGES

- Interior & exterior use.
- Good adhesion.
- Ready to use.
- Smooth finished.
- Quick drying.
- Not easy to cracks.
- Can paint it over.

### TECHNICAL PROPERTIES

Color:	White
Form:	Paste
Specific gravity:	1.60 – 1.65
Solid content:	~100%
pH value:	8 – 9
Application temp:	5°C – 50°C

### SURFACE PREPARATION

The substrate must be sound, clean free from oil, grease, mould oil, dust, and loose particles and cement paste.

### APPLICATION

Apply material by spatula or steel trowel.

### PACKAGING

5 kg.

### STORAGE

Storage in shade and dry condition at 10-40°C. Avoid from sunlight, frost, water, moisture and high temperature.

### SHELF LIFE

12 months un-open container and kept follow instruction.



### PRECAUTIONS

Keep out of reach of children. Do not breathe dust. If swallowed, seek medical advice immediately and show this container or label.

### CONTACT DETAIL

#### THAILAND

#### **Rockmax Company Limited**

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

#### VIETNAM

#### **Viet Dai Viet Chemical Company Limited**

T: +84862615184


F: +84862615185

E: rockmaxvn@gmail.com

---

#### *IMPORTANT NOTE!!*

*The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.*

 Printed on recycled paper  
Copyright©2012 Rockmax