

ROCKMAX[®] TOP200

ONE PART SKIM RENDER POWDER



INTRODUCTION

Rockmax TOP200 is a ready to use one part skim smooth surface rendering powder form. It can be applied both internal and external surfaces. **Rockmax TOP200** provides a thin fairing surface over hairline crack, pinholes, air pocket, seams and minor defected surfaces.

AREA OF USES

- Cast in place concrete surfaces.
- Pre cast concrete surfaces.
- Over rendering mortar surfaces.
- All cementitious substrates.

ADVANTAGES

- Good adhesion.
- Can use both internal & external.
- Easy to apply.
- Good smooth & fine surface.
- Can over paint.

TECHNICAL PROPERTIES

Color & Form: Grey powder
Specific Gravity: approx 1.05
Pot life (30°C): approx 30-35 minute
Mix with water: 37-40% by weight
Thickness per layer: 0.5-4.0mm
Working temperature: 5°C-35°C degree
Coverage rate: 1.2 – 1.4kg/m²/mm
(Coverage rate depend on condition of surfaces)

PREPARATION

Concrete substrate must be clean and free from oil, grease, dust, particles, mould oil, curing compound. Soak water until concrete saturated.

MIXING

Mixer must use low speed drill mixer (500 rpm) with and including good quality steel paddle. Make sure all tools and equipments are in good conditions and clean. Measure 7.4 – 8.0litre of clean water for 20kg bag of **Rockmax TOP200**. Add material slowly into water while mixing. Mix continuous for approximate 3 minute until homogeneous. The mixing ratio could be adjusted according to user and environment conditions.

APPLICATION

Apply mortar by steel trowel. Multi layer could be applied.

CURING

Wait to dry for 7 days prior to paints.

CLEANING

Clean all tools and equipment immediately after application with water.

LIMITATIONS

- Do not apply on gypsum board.
- In high temperature, the applied area must be protected for drying up by plastic bag or spray water.

PACKAGING

20kg bag.

STORAGE

Storage in shade and dry condition Avoid from frost, water, moisture and high temperature.

SHELF LIFE

12 months if kept follow instructions.

PRECAUTIONS

Avoid contact with skin and eye. Goggle and glove must be use while application. Standard safety precautions must be followed. Clean with plenty of water when contact with mortar and see doctor as quick as possible.

CONTACT DETAIL

THAILAND

Rockmax Company Limited

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

VIETNAM

Viet Dai Viet Chemical Company Limited

T: +84 86 2615184

F: +84 86 2615185

E: rockmaxvn@gmail.com

IMPORTANT NOTE!!

The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.
