

# ROCKMAX<sup>®</sup> SUPERCOTE ASP

WATER BASED EPOXY PRIMER FOR ANTISTATIC FLOOR



## INTRODUCTION

**Rockmax Supercote ASP** is a water dispersed two component, low viscosity, epoxy primer. It use as primer for antistatic floor system.

## AREA OF USES

**Rockmax Supercote ASP** use for priming concrete substrate prior to apply antistatic floor system.

## ADVANTAGES

- Low viscosity,
- Good penetration to concrete substrate.
- Good adhesion.
- Easy to apply.
- Water based product.

## TECHNICAL PROPERTIES

Color: black

Bond strength: > 1.7 N/mm<sup>2</sup>

Pot life (at 25°C): approx 45 minutes

Working temperature: 10°C - 35°C

Touch dry (at 25°C): 6 hours

Foot traffic (at 25°C): 24 hours

No of coats: 1 coat

Coverage rate: 0.20 kg/m<sup>2</sup>/coat

## PREPARATION

Concrete must be sound, clean and free from cement paste, dust, dirt and any other contaminants. Concrete must be at least 28 days and minimum Compressive strength 25N/mm<sup>2</sup> and minimum tensile strength (pull off) at 1.5 N/mm<sup>2</sup>.

## MIXING

Mix part A and part B approximate 3 minutes until homogeneous using electric mixer (400-500 rpm).

## APPLICATION

Apply by brush or roller on the prepared surface. Wait until dry 24 hours prior to apply body coat.

## CLEANING

Clean all tools and equipments immediately with clean water.

## PACKAGING

5kg set.

## STORAGE

Storage in shade and dry condition at 10-30°C. Avoid from sunlight, frost, water, moisture and high temperature.

## SHELF LIFE

12 months if kept in original package and proper storage area.

## PRECAUTIONS

Avoid contact with skin and eye. Avoid inhalation. Harmful effects may cause during application and care must be taken. Ventilation must be provided.

## CONTACT DETAIL

**Rockmax Company Limited (Thailand)**

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

## Exclusive Distributor Vietnam

**Viet Dai Viet Chemical Company Limited**

311 Ton Dan Street, Ward 15, District 4,  
Ho Chi Minh City, Vietnam

T: +84862615184

F: +84862615185

E: rockmaxvn@gmail.com

---

### IMPORTANT NOTE!!

*The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.*

---