

# ROCKMAX<sup>®</sup> MOFORM W

## WATER BASED MOULD RELEASE AGENT



### INTRODUCTION

**Rockmax Moform W** is a water based mould release agent. It is formulated from blended emulsion and mineral materials. Product provides water repellent surface achieve clear and easy to remove formworks.

### AREA OF USES

**Rockmax Moform W** can be used for wood and steel formworks.

### ADVANTAGES

- Provide fare face concrete.
- Easy to use.
- Economical.
- Non toxic.
- Non staining.

### TECHNICAL PROPERTIES

Color and Form: Clear or Milky white liquid

Specific Gravity: 0.99

Coverage rate:

Wood surface: 10 m<sup>2</sup> / litre

Steel surface: 18 m<sup>2</sup> / litre

### SURFACE PREPARATION

Form surfaces must be clean and free from dust, dirt, oil and cement paste.

### APPLICATION

Apply **Rockmax Moform W** by brush or roller. Protect the coated area from rainfall. Drying time depend on temperature and humidity.

### CLEANING

Clean all tools and equipments by clean water.

### PACKAGING

210 litre steel drum.

### STORAGE

Storage in shade and dry condition at 10-40°C. Avoid from sunlight, frost, water, moisture and high temperature.

### SHELF LIFE

12 months if kept in original package and proper storage area.

### PRECAUTIONS

**Rockmax Moform W** is not hazardous material. However avoid contact with skin and eyes. Safety goggles and gloves must be used during application. In case of skin of eye contact, rinse with plenty of water and see medical immediately. If swallowed must be see medical immediately. Do not induce vomiting. **Rockmax Mofrom W** is not flammable.

### CONTACT DETAIL

**Rockmax Company Limited (Thailand)**

T: +66 2 8648658

F: +66 2 4184327


E: [info@rockmax.net](mailto:info@rockmax.net)

W: [www.rockmax.net](http://www.rockmax.net)

---

### IMPORTANT NOTE!!

*The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.*

 Printed on recycled paper  
Copyright©2009 Rockmax